



NOTES:
 1. 1500°F MAX
 2. 32" STAINLESS STEEL
 BRAIDED LEAD

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 ELECTRONIC DEVELOPMENT LABS. ANY
 REPRODUCTION IN PART OR AS A WHOLE
 WITHOUT THE WRITTEN PERMISSION OF
 ELECTRONIC DEVELOPMENT LABS IS
 PROHIBITED.

Revision History			
REV	Description	Date	By:
0	ISSUED	8/8/2016	LB

UNLESS OTHERWISE SPECIFIED:
TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° BEND ± 1° TWO PLACE DECIMAL ± .02 THREE PLACE DECIMAL ± .005
RAW MTRL NOTES:
MATERIAL: STAINLESS STEEL/CERAMIC
FINISH:

The Temperature People
ELECTRONIC DEVELOPMENT LABS. INC.
 & E. D. L. TOOL & DIE
 244 Oakland Drive, Danville VA, 24540

TITLE: NH-15GSOKK2M NEEDLE SENSOR		
SIZE A	DWG. NO. NH15GSOKK2M	REV 0
SCALE: 1:1	UNITS: INCHES	SHEET 1 OF 1

5

4

3

2

1